

TECHNICAL INFORMATION

Technical Specifications

Technical Specifications			
Hammer Model		AR 48	AR 62
Frequency Range	blows per minute	700 - 1500	450 - 1150
Hydraulic Flow	gpm (lpm)	4 - 9 (15 - 35)	6 - 12 (23 - 45)
Hydraulic Operating Pressure	psi (bar)	1300 - 1750 (90 - 120)	1300 - 1900 (90 - 130)
Precharge Chamber N2 Pressure	psi (bar)	185 (12.8) at 70 F (21 C) 215 (15.0) at 150 F (65 C)	150 (10.3) at 70 F (21 C) 175 (12.0) at 150 F (65 C)
Weight - Mini-Excavator	lbs. (kg)	320 (145)	440 (200)
Working Length Mini-Excavator	in. (mm)	46.2 (1174)	55.9 (1420)
Weight - Skid Steer	lbs. (kg)	600 (272)	670 (304)
Working Length Skid Steer	in. (mm)	42.0 (1066)	47.1 (1197)
Demolition Tool Diameter	Type in. (mm)	Conical 1.89 (48)	Conical 2.44 (62)
Working Length	in. (mm)	12 (305)	15 (380)
Carrier Weight Class Excavator	1000 lbs (1000 kg)	4 - 8 (1.8 - 3.6)	6 - 10 (2.7 - 4.5)
Carrier Weight Class Skid Steer	1000 lbs (1000 kg)	3 - 6 (1.3 - 2.7)	4 - 6 (1.8 - 2.7)
Hydraulic Hose Size	In. (mm)	½ in. (13mm)	½ in. (13mm)